

PRODUCT DESCRIPTION

MIDSUMMER **BOLD**



A magnificent solar panel

Midsummer BOLD is exceptionally suitable for larger installations in private homes as well as commercial buildings. It is optimal for roofs with weight and wind restrictions and fits on most types of flat roofs.

With Midsummer BOLD's thinness and flexibility you don't have to compromise between elegance and efficiency. With our factory in Järfälla and effective production process we have also managed to cut the CO2 emissions by almost 90 %, compared to traditional solar panels.

All this with a 10 year product warranty and a 80 % efficiency warranty for 25 years. A solar roof to count on.



Facts

Nominal power, Pm ($\pm 2,5W$)	205 Wp
Wp/m ²	121 Wp
Voltage at max power, (V)	31,0 V
Current at max power, (A)	6,54 A
Voltage at open circuit, Voc	35,5 V
Current at short circuit, Isc	7,7 A
Temperature coefficient, Pm (W)	-0,351 %/°C
Temperature coefficient, Voc (V)	-0,305 %/°C
Temperature coefficient, Isc (A)	-0,011 %/°C

Article information

Weight	3 kg/m²
Width	1 000 mm
Length	1 685 mm
Thickness	ca 2 mm
Roof pitch	0°
Cell type	Thin film CIGS
Color	Black
Product warranty	10 years

